## NSN 4720-00-111-8874

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-111-8874

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.830 inches
Minimum Inside Bending Radius:
2.250 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
3500.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided fabric and 1st layer braided textile yarn
Maximum Operating Pressure:
875.0 pounds per square inch
Thread Size:
0.875 inches 1st end
Seat Angle:
45.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
56.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon and air and water single response

Unf 1st end

**Thread Series Designator:** 

## NSN 4720-00-111-8874

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0