

View Online at <https://aerobasegroup.com/nsn/4720-00-113-5478>

Cross Sectional Shape:

Round

Inside Diameter:

1.500 inches

Outside Diameter:

2.125 inches

First End Fitting Specification/std Data:

Mil ms27025-9 standard (includes industry or association standards, individual manufactureer standards, etc.).

Second End Fitting Specification/std Data:

Mil ms27021-9 standard (includes industry or association standards, individual manufactureer standards, etc.).

Quick Disconnect Size:

1.500 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting aluminum alloy all ends

Connection Type:

Internal quick disconnect 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Not identical

Burst Test Pressure:

500.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber

Hydrostatic Test Pressure:

150.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and oil resistant and mildew resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Specification Data:

81349-mil-h-370 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0