NSN 4720-00-114-0916

Nonmetallic Hose Assembly - Page 1 of 2



View C	Online at https://aerobasegroup.com/nsn/4720-00-114-0916
Cross	Sectional Shape:
Round	
Threa	d Class:
2b 1st	end
Threa	d Direction:
Right-l	hand 1st end
Inside	Diameter:
0.298	inches
Temp	urature Rating:
-65.0 c	degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outsid	de Diameter:
0.656	inches
Minim	um Inside Bending Radius:
2.500	inches
Conne	ection Style:
Swivel	nut flare 1st end
End C	onnection Design:
Straigh	nt 1st end
Conne	ection Type:
Thread	ded internal tube 1st end
Featu	res Provided:
Electro	ostatic discharge capability
Burst	Test Pressure:
14000	.0 pounds per square inch
Layer	Composition And Location:
Outer	layer braided corrosion resistant steel wire
Maxim	num Operating Pressure:
3000.0) pounds per square inch
Threa	d Size:
0.562	inches 1st end
Seat A	Angle:
37.0 d	egrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant and fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

8.500 inches working

Thread Series Designator:

Unjf 1st end

NSN 4720-00-114-0916

Nonmetallic Hose Assembly - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81343-as153 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0