NSN 4720-00-114-3408

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-114-3408 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.594 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided textile yarn and outer layer rubber impregnated woven fabric and 1st layer braided textile yarn **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and weatherproof **Inside Surface Condition:** Smooth **Measuring Method And Length:**

Media For Which Designed:

24.250 inches

Fuel/oil, hydrocarbon single response

NSN 4720-00-114-3408

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Design	nator:
	0000	-00.9.	

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0