NSN 4720-00-115-8992



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-115-8992 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.125 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.470 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 2nd layer rubber impregnated braided fabric and outer layer molded rubber, chloroprene and 1st layer rubber impregnated braided fabric **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:**

0.438 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

NSN 4720-00-115-8992

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0