Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-116-0063

Cross See	ctional Shape:
Round	
Thread Cl	ass:
2a 1st end	l de la constante de
Thread Di	rection:
Right-hand	d 1st end
Inside Dia	imeter:
0.188 inch	es
Tempurat	ure Rating:
-40.0 degr	ees fahrenheit and 212.0 degrees fahrenheit single response
Outside D	Diameter:
0.386 inch	es
Exterior C	Color:
Black	
Connectio	on Style:
Swivel nut	, inverted flare 1st end
End Conn	nection Design:
Straight 1s	st end
Connectio	on Type:
Threaded	external tube 1st end
Burst Tes	t Pressure:
700.0 pou	nds per square inch
Layer Cor	nposition And Location:
2nd layer l	braided fabric and outer layer molded rubber, synthetic and 1st layer braided fabric
Maximum	Operating Pressure:
175.0 pou	nds per square inch
Thread Si	ze:
0.375 inch	les 1st end
Seat Angl	e:
45.0 degre	ees 1st end
Hydrosta	tic Test Pressure:
350.0 pou	nds per square inch
Inside Su	rface Condition:
Smooth	
Measuring	g Method And Length:
35.500 inc	hes
Media For	r Which Designed:
	ydrocarbon single response
	eries Designator:
Unf 1st en	-
Shelf Life	:
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0