Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-116-3225

reas Castienal Change	
ross Sectional Shape:	
ound	
hread Direction:	
ight-hand 1st end	
side Diameter:	
250 inches	
empurature Rating:	
0.0 degrees fahrenheit and 225.0 degrees fahrenheit single response	
utside Diameter:	
468 inches	
inimum Inside Bending Radius:	
500 inches	
onnection Style:	
lain 1st end	
nd Connection Design:	
traight 1st end	
onnection Type:	
nreaded external pipe 1st end	
urst Test Pressure:	
00.0 pounds per square inch	
ayer Composition And Location:	
uter layer molded rubber, synthetic and 1st layer braided cotton cord	
aximum Operating Pressure:	
75.0 pounds per square inch	
hread Size:	
125 inches 1st end	
uter Covering Environmental Protection:	
brasion resistant and fuel resistant and oil resistant and water resistant and weather	proof
side Surface Condition:	
mooth	
easuring Method And Length:	
0.000 inches	
edia For Which Designed:	
uel/oil, hydrocarbon single response	
hread Series Designator:	
pt 1st end	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	

NSN 4720-00-116-3225

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

