## NSN 4720-00-116-6811

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-116-6811

Cross Sectional Shape:
Round
Thread Class:
2a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Minimum Inside Bending Radius:
4.620 inches
Exterior Color:
Gray
Connection Style:
Flared 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Reusable end fittings
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
50.875 inches

Fuel/oil, hydrocarbon single response

Media For Which Designed:

## NSN 4720-00-116-6811

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series	Designator:
Unf 1st end	

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0