Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-118-1505

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.313 inches |
| Tempurature Rating: |
| -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.446 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Exterior Color: |
| Natural |
| Angle Between Rigid Elbow Fittings In Deg: |
| 45.0 |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Electrostatic discharge capability |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.562 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Vacuum In Torr: |
| |

50.8

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Inside Surface Condition: Smooth

Measuring Method And Length:

11.500 inches working

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms8000 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0