Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-119-0484

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Minimum Inside Bending Radius:

4.500 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-13531, type 2 or 3, class a or b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil mil-h-13531 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Swivel nut flare 1st end End Connection Design: Straight 1st end

Connection Style:

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

17000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Maximum Operating Pressure:

4250.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

8500.0 pounds per square inch

Outer Covering Environmental Protection

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 34.000 inches working **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end **Specification Data:** 96906-ms500083 government standard Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0