NSN 4720-00-119-3707

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-119-3707

view Offilite at https://aerobasegroup.com/hish/+//20-00-119-0/0/
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches
Tempurature Rating:
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Hose Or Tubing Specification/std Data:
Mil mil-h-5593 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Mil ms27404-2d standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Socket aluminum alloy all ends
Fitting Component And Surface Treatment:
Socket anodize 2nd end
Connection Type:
Threaded internal tube 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
2000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
Outer layer molded rubber
Maximum Operating Pressure:
300.0 pounds per square inch

Seat Angle: 37.0 degrees 1st end

0.312 inches 1st end

Thread Size:

NSN 4720-00-119-3707

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure: 600.0 pounds per square inch **Outer Covering Environmental Protection:** Abrasion resistant and fuel resistant and oil resistant **Vacuum In Torr:** 254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 48.500 inches working **Special Features:** Inner conveying tube material-rubber, synthetic Media For Which Designed: Air single response **Thread Series Designator:** Unf 1st end **Specification Data:** 88044-an6270 government standard Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A542a0