Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-122-4193

Cross	s Sectional Shape:
Round	d
Threa	d Direction:
Right-	hand 1st end
Inside	e Diameter:
Betwe	een 0.485 inches and 0.531 inches
Temp	purature Rating:
-40.0	degrees fahrenheit and 200.0 degrees fahrenheit single response
Outsi	de Diameter:
Betwe	een 0.938 inches and 1.000 inches
Minin	num Inside Bending Radius:
7.000	inches
Conn	ection Style:
Invert	ed flare 1st end
End C	Connection Design:
Straig	ht 1st end
Conn	ection Type:
Threa	ded external pipe 1st end
Burst	Test Pressure:
14000	0.0 pounds per square inch
Layer	Composition And Location:
2nd la	yer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire
Maxir	num Operating Pressure:
3500.	0 pounds per square inch
Threa	nd Size:
0.500	inches 1st end
Seat	Angle:
30.0 c	degrees 1st end
Hydro	ostatic Test Pressure:
7000.	0 pounds per square inch
Inside	e Surface Condition:
Smoo	th
Meas	uring Method And Length:
43.50	0 inches
Media	a For Which Designed:
Fuel/c	bil, hydrocarbon single response
Threa	nd Series Designator:
Npt 1	st end
Shelf	Life:
N/a	
Unit (	Of Measure:

## NSN 4720-00-122-4193

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

