

View Online at <https://aerobasegroup.com/nsn/4720-00-122-4204>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.985 inches and 1.040 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.312 inches 2nd end

Outside Diameter:

Between 1.516 inches and 1.609 inches

Recess Diameter:

1.937 inches 1st end

Recess Depth:

0.125 inches 2nd end

Minimum Inside Bending Radius:

12.000 inches

Flange Outside Diameter:

2.000 inches 1st end

Connection Style:

Recessed w/gasket groove 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Recessed flange 2nd end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire

Maximum Operating Pressure:

2000.0 pounds per square inch

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

39.000 inches

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0