## NSN 4720-00-122-4213

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-122-4213
Cross Sectional Shape:
Round
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.313 inches 2nd end
Outside Diameter:
1.609 inches
Minimum Inside Bending Radius:
12.000 inches
Angle Between Rigid Elbow Fittings In Deg:
0.0
Flange Outside Diameter:
2.000 inches 1st end
Connection Style:
Plain w/ gasket groove (sae flanged head) 2nd end
End Flange Construction:
Solid 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Plain face flange 2nd end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
27.750 inches
Flange Style:
Round w/ out bolt holes 2nd end

**Media For Which Designed:** 

Fuel/oil, hydrocarbon single response

## NSN 4720-00-122-4213

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0