Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-122-4214

С	cross Sectional Shape:
	tound
	hread Direction:
	light-hand 1st end
Ir	nside Diameter:
0	.500 inches
Т	empurature Rating:
-4	40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
0	Dutside Diameter:
0	.968 inches
N	linimum Inside Bending Radius:
7	.000 inches
Ε	xterior Color:
В	lack
С	connection Style:
Ir	overted flare 1st end
Ε	Ind Connection Design:
S	traight 1st end
С	Connection Type:
Т	hreaded external pipe 1st end
В	Burst Test Pressure:
1	4000.0 pounds per square inch
L	ayer Composition And Location:
2	nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire
N	laximum Operating Pressure:
3	500.0 pounds per square inch
Т	hread Size:
0	.500 inches 1st end
S	eat Angle:
3	0.0 degrees 1st end
Н	lydrostatic Test Pressure:
7	000.0 pounds per square inch
0	Outer Covering Environmental Protection:
0	Dil resistant and weatherproof
Ir	nside Surface Condition:
S	Smooth
N	leasuring Method And Length:
2	8.375 inches
M	ledia For Which Designed:
Н	lydraulic fluid single response
т	hread Series Designator:
N	lptf 1st end

NSN 4720-00-122-4214

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

