

View Online at <https://aerobasegroup.com/nsn/4720-00-122-5671>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.560 inches

Temperature Rating:

-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

0.920 inches

Minimum Inside Bending Radius:

6.500 inches

Exterior Color:

Natural

Connection Style:

Swivel nut, flareless 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and 2nd layer spirally wrapped polytetrafluoroethylene impregnated glass fiber and 3rd layer spirally wrapped polytetrafluoroethylene impregnated glass fiber and 4th layer spirally wrapped polytetrafluoroethylene impregnated glass fiber and outer layer spirally wrapped polytetrafluoroethylene impregnated glass fiber

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.875 inches 2nd end

Seat Angle:

12.0 degrees 2nd end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Ethylene glycol resistant and fuel resistant and oil resistant and fuel resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches working

Special Features:

Special sleeve p/n 900223

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0