NSN 4720-00-123-0563

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-123-0563 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.344 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.563 inches **Minimum Inside Bending Radius:** 2.500 inches **Exterior Color:** Natural Angle Between Rigid Elbow Fittings In Deg: 90.0 **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial coverage **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.563 inches 2nd end Seat Angle: 37.0 degrees 2nd end Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** Corrosion resistant **Inside Surface Condition:**

7.750 inches

Measuring Method And Length:

Smooth

NSN 4720-00-123-0563

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0