
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-123-3452

Cros	ss Sectional Shape:
Rou	nd
Thre	ead Class:
3b 1	st end
Thre	ead Direction:
Righ	t-hand 1st end
Insid	de Diameter:
0.37	5 inches
Outs	side Diameter:
0.53	1 inches
Con	nection Style:
Swiv	el nut flare 1st end
End	Connection Design:
Strai	ght 1st end
Con	nection Type:
Thre	aded internal hose 1st end
Thre	eady Qty Per Inch (tpi):
20 1	st end
Burs	st Test Pressure:
1500).0 pounds per square inch
Laye	er Composition And Location:
Oute	er layer molded rubber, synthetic and 1st layer braided cotton cord
Мах	imum Operating Pressure:
275.	0 pounds per square inch
Thre	ad Size:
0.50	0 inches 1st end
Hyd	rostatic Test Pressure:
300.	0 pounds per square inch
Oute	er Covering Environmental Protection:
Abra	sion resistant and mildew resistant
Insid	de Surface Condition:
Smo	oth
Mea	suring Method And Length:
25.1	25 inches working and 25.375 inches working
Med	ia For Which Designed:
Hydı	aulic fluid single response
Thre	ad Series Designator:
Unf	1st end
She	If Life:
N/a	

NSN 4720-00-123-3452

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0