
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-123-3469

Cross Se	ctional Shape:
Round	
Thread C	ass:
3b 1st end	
Thread Di	rection:
Right-hand	1 1st end
Inside Dia	meter:
0.375 inch	es
Outside D	iameter:
0.531 inch	es
Connectio	on Style:
Swivel nut	flare 1st end
End Conr	ection Design:
Straight 1s	st end
Connectio	on Type:
Threaded	internal hose 1st end
Thready (Qty Per Inch (tpi):
20 1st end	
Burst Tes	t Pressure:
1500.0 po	unds per square inch
Layer Cor	nposition And Location:
Outer laye	r molded rubber, synthetic and 1st layer braided cotton cord
Maximum	Operating Pressure:
275.0 pou	nds per square inch
Thread Si	ze:
0.500 inch	es 1st end
Hydrosta	ic Test Pressure:
300.0 pou	nds per square inch
Outer Cov	vering Environmental Protection:
Abrasion r	esistant and mildew resistant
Inside Su	rface Condition:
Smooth	
Measurin	g Method And Length:
23.790 inc	hes working and 24.100 inches working
Media Fo	Which Designed:
Hydraulic	fluid single response
Thread Se	eries Designator:
Unf 1st en	d
Shelf Life	:
N/a	
Linit Of M	easure:

NSN 4720-00-123-3469

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

