Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-126-4585

view online at https://delobdoegloup.com/hon/+/20 00 120 4000
Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer molded rubber, synthetic and 1st layer braided steel wire
Maximum Operating Pressure:
4000.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Fire resistant and oil resistant and water resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
43.000 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

## NSN 4720-00-126-4585

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

