

View Online at <https://aerobasegroup.com/nsn/4720-00-128-0407>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.375 inches

Minimum Inside Bending Radius:

2.000 inches

Exterior Color:

Black

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Thread Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene and 1st layer spirally laid cotton cord

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

1000.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and cold resistant and grease resistant and light resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.500 inches

Special Features:

Furnished w/one adapter straight thd 0.438-24 uns 2b to 0.125-27 npt 2a

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0