Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-129-6686

Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.220 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 160.0 degr	ees fahrenheit single response
Outside Diameter:	
0.625 inches	
Minimum Inside Bending Radius:	
3.000 inches	
Exterior Color:	
Black	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Perforated outer cover	
Burst Test Pressure:	
20000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided corrosion resistant stee	el wire and outer layer molded rubber and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:	
5000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
10000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
14.375 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0