

View Online at <https://aerobasegroup.com/nsn/4720-00-130-4475>

Cross Sectional Shape:

Round

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Outside Diameter:

0.781 inches

Minimum Inside Bending Radius:

5.000 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, synthetic and 1st layer braided steel wire

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.562 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Cold resistant and heat resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

39.000 inches working

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0