

View Online at <https://aerobasegroup.com/nsn/4720-00-131-2883>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Outside Diameter:**

0.375 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Natural

**Angle Between Rigid Elbow Fittings In Deg:**

230.0

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

10000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

36.5 degrees 1st end and 37.5 degrees 1st end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

31.880 inches working and 32.380 inches working

**Thread Series Designator:**

Unjf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A542a0