NSN 4720-00-131-2883

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-131-2883

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Angle Between Rigid Elbow Fittings In Deg:
230.0
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
36.5 degrees 1st end and 37.5 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Vacuum In Torr:
50.8
Inside Surface Condition:

Smooth

NSN 4720-00-131-2883

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

31.880 inches working and 32.380 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A542a0