## NSN 4720-00-131-6454

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-131-6454 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Inside Diameter: 0.313 inches **Outside Diameter:** 0.446 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Natural Angle Between Rigid Elbow Fittings In Deg: **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Elbow 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1500.0 pounds per square inch **Thread Size:** 0.562 inches 1st end Seat Angle: 36.5 degrees 1st end and 37.5 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Vacuum In Torr:** 50.8

Inside Surface Condition:

Smooth

## NSN 4720-00-131-6454

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	000	igilatoi.

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0