

View Online at <https://aerobasegroup.com/nsn/4720-00-133-2305>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 2nd end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

Between 0.235 inches and 0.265 inches

**Temperature Rating:**

-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response

**Outside Diameter:**

Between 0.367 inches and 0.406 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

155.0

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Threaded internal tube 2nd end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

20 1st end

**Burst Test Pressure:**

10000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1500.0 pounds per square inch

**Thread Size:**

0.500 inches 1st end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

3000.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Special Features:**

W/black thermo-fit polyolefin chafe guard

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0