

NSN 4720-00-134-8882 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-134-8882 **Cross Sectional Shape:** Round

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
35.750 inches working

NSN 4720-00-134-8882

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8000 government standard
Shelf Life:
N/a

Demilitarization:

Unit Of Measure:

No

Fiig:

A542a0