NSN 4720-00-135-0620

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-135-0620

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.422 inches and 0.462 inches
Outside Diameter:
Between 0.781 inches and 0.843 inches
Minimum Inside Bending Radius:
8.000 inches
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Thready Qty Per Inch (tpi):
12 1st end
Layer Composition And Location:
2nd layer spirally laid corrosion resistant steel wire and outer layer braided corrosion resistant steel wire and 1st layer braided corrosion
resistant steel wire
Maximum Operating Pressure:
4500.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Hydrostatic Test Pressure:
9000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Criticality Code Justification:
Zzzy
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.250 inches and 18.750 inches
Special Markings:
678619-8-0184l1
Thread Series Designator:
Un 1st end
Reference Number Differentiating Characteristics:

Quality control iaw navships 0948-045-7010 material identification and control instruction for level 1 items

N/a

Shelf Life:

NSN 4720-00-135-0620

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0