Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-135-8883

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
0.438 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Connection Style:	
Swivel nut, inverted flare 1st end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal pipe 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
2000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer molded rubber, synthetic and 1st layer braided textile yarn	
Maximum Operating Pressure:	
500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
1000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Cold resistant and oil resistant and ozone resistant and weatherproof	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
24.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 2nd end	

## NSN 4720-00-135-8883

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

