Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-136-4447

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Tempurature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

1.250 inches

Minimum Inside Bending Radius:

9.500 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability and reusable end fittings

Thready Qty Per Inch (tpi):

12 2nd end

Burst Test Pressure:

9000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and 1st layer braided wire

Maximum Operating Pressure:

2250.0 pounds per square inch

Thread Size:

1.062 inches 2nd end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

4500.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and cold resistant and mildew resistant and oil resistant and ozone resistant

NSN 4720-00-136-4447

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 45.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Un 2nd end Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0