Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-136-5222

# Cross Sectional Shape:

Round

Thread Class:

3b 1st end

# Thread Direction:

Right-hand 1st end

# Inside Diameter:

0.620 inches

### **Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

# **Outside Diameter:**

1.080 inches

**Exterior Color:** 

Black

### **Connection Style:**

Swivel nut flare 1st end

# End Connection Design:

Straight 1st end

# **Connection Type:**

Threaded internal tube 1st end

# Features Provided:

Electrostatic discharge capability

# Thready Qty Per Inch (tpi):

12 1st end

# **Burst Test Pressure:**

6000.0 pounds per square inch

# Layer Composition And Location:

1st layer braided textile yarn and 2nd layer braided steel wire and 3rd layer braided textile yarn and outer layer molded rubber, synthetic

# Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

1.062 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

3000.0 pounds per square inch

# **Outer Covering Environmental Protection:**

Abrasion resistant and mildew resistant and oil resistant

# Vacuum In Torr:

50.8

# Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



# Measuring Method And Length:

12.000 inches

# Media For Which Designed:

Butane and fuel/oil, hydrocarbon and water, fresh and water, salt single response

## Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

### Demilitarization:

No

### Fiig:

A542a0