NSN 4720-00-136-7257

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-136-7257

Cross Sectional Shape:
Round
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.422 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response
Outside Diameter:
0.815 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Natural
Connection Style:
External seat for gasket seal (boss) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external boss 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
22000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and 2nd layer spirally laid corrosion resistant steel wire and 3rd layer spirally laid corrosion
resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
4500.0 pounds per square inch
Thread Size:
1.750 inches 1st end
Seat Angle:
90.0 degrees 1st end
Hydrostatic Test Pressure:
9000.0 pounds per square inch
Outer Covering Environmental Protection:
Abracion resistant and weatherproof

Smooth

Inside Surface Condition:

NSN 4720-00-136-7257

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
17.000 inches
Special Features:
Cleaned and packaged in polyethylene tube
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0