NSN 4720-00-138-5463



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-138-5463 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.188 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response **Outside Diameter:** 0.516 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 12000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided fabric and outer layer rubber impregnated cotton fabric and 1st layer braided cotton cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Vacuum In Torr:** 28.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 21.500 inches Media For Which Designed: Air and fuel/oil, hydrocarbon single response **Thread Series Designator:**

Unf 1st end Shelf Life:

N/a

NSN 4720-00-138-5463

Nonmetallic Hose Assembly - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A542a0