NSN 4720-00-139-3932

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-139-3932

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Flange Thickness:
0.325 inches 2nd end
Outside Diameter:
1.525 inches
Minimum Inside Bending Radius:
12.000 inches
Exterior Color:
Black
Flange Outside Diameter:
2.000 inches 2nd end
Connection Style:
Swivel nut flare 1st end
End Flange Construction:
Solid 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and outer layer molded rubber, synthetic and 1st layer braided wire
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
1.312 inches 1st end
Seat Angle:
37.0 degrees 1st end

NSN 4720-00-139-3932

Nonmetallic Hose Assembly - Page 2 of 2



Hydrostatic Test Pressure:
4000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
147.000 inches
Flange Style:
Round w/ out bolt holes 2nd end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0