Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-139-4159

Cross Sectional Shape	:
-----------------------	---

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

0.580 inches

Minimum Inside Bending Radius:

3.380 inches

Exterior Color:

Black

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

10000.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer rubber impregnated braided fabric and 1st layer braided fiber

Maximum Operating Pressure:

2500.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

5000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

63.500 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Air and water and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0