Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-140-4258

View Online at https://aerobasegroup.com/nsn/4/20-00-140-4258
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.310 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.670 inches
Minimum Inside Bending Radius:
3.120 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided wire and outer layer rubber impregnated cotton fabric and 1st layer braided textile yarn
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
70.250 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by magnetic permeability shall be less than 1.2 before fabrication and not greater than 2.0 oersted field by permeability

indicator specified in military specification mil-i-17214

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0