NSN 4720-00-141-3228

78.000 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-141-3228

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.688 inches
Tempurature Rating:
-65.0 degrees celsius and 158.0 degrees celsius single response
Outside Diameter:
1.219 inches
Minimum Inside Bending Radius:
7.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided steel wire and outer layer molded rubber, chloroprene and 1st layer braided steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:

NSN 4720-00-141-3228

Nonmetallic Hose Assembly - Page 2 of 2



V	ledia	For	Whi	ich	Des	ian	ed:
٧	ieuia	TO1	VVII	ICH	Des	uun	eu.

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Specification Data:

96906-ms8759 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0