Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-142-1247

Cross	Sectional	Shape:

Round

**Thread Class:** 

2b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.219 inches

## **Outside Diameter:**

0.438 inches

**Connection Style:** 

Swivel nut flare 1st end

#### End Connection Design:

Straight 1st end

#### Connection Type:

Threaded internal tube 1st end

#### **Features Provided:**

Electrostatic discharge capability

#### **Burst Test Pressure:**

6000.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

## Maximum Operating Pressure:

1500.0 pounds per square inch

### Thread Size:

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

#### **Outer Covering Environmental Protection:**

Abrasion resistant and corrosion resistant

### Inside Surface Condition:

Smooth

#### Measuring Method And Length:

15.750 inches working

#### Media For Which Designed:

Fuel/oil, hydrocarbon single response

# **Thread Series Designator:**

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

# NSN 4720-00-142-1247

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

