Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-142-1257

Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.438 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degree	es fahrenheit single response
Outside Diameter:	
0.641 inches	
Minimum Inside Bending Radius:	
3.500 inches	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
5000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided corrosion resistant steel	wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
2500.0 pounds per square inch	
Flow Angle:	
45.0 degrees 1st end	
Outer Covering Environmental Protecti	on:
Corrosion resistant and fire retardant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
19.500 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	

Nonmetallic Hose Assembly - Page 2 of 2

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

