

View Online at <https://aerobasegroup.com/nsn/4720-00-142-2149>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

**Outside Diameter:**

1.234 inches

**Minimum Inside Bending Radius:**

7.375 inches

**Exterior Color:**

Black

**Connection Style:**

Swivel nut flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Reusable end fittings

**Thready Qty Per Inch (tpi):**

12 2nd end

**Burst Test Pressure:**

3200.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and outer layer rubber impregnated braided fabric and 1st layer braided fiber

**Maximum Operating Pressure:**

800.0 pounds per square inch

**Thread Size:**

1.312 inches 2nd end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

1600.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and hydraulic solution resistant and mildew resistant and oil resistant

**Vacuum In Torr:**

50.8

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

7.688 inches

**Seat Radius:**

0.031 inches 2nd end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0