

View Online at <https://aerobasegroup.com/nsn/4720-00-142-2561>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.500 inches

Temperature Rating:

-40.0 degrees fahrenheit single response

Outside Diameter:

1.188 inches

Quick Disconnect Size:

0.500 inches 2nd end

Connection Style:

Universal 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Universal quick disconnect 2nd end

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

2nd layer braided fabric and outer layer molded rubber, synthetic and 1st layer braided fabric

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Hydrostatic Test Pressure:

300.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

120.000 inches excluding end fittings

Special Features:

Couplings attached with 2 bolt finger type clamps

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Thread Series Designator:

Npt 1st end

Specification Data:

81348-zz-h-550 government specification

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0