

View Online at <https://aerobasegroup.com/nsn/4720-00-142-5343>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Outside Diameter:

0.750 inches

Hose Or Tubing Specification/std Data:

Mil-h-3992, type 1, class 1 or 2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Quick Disconnect Size:

0.427 inches 2nd end

Connection Style:

Push (internal) 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting steel all ends

Connection Type:

Threaded external pipe 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

900.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Thread Size:

0.250 inches 1st end

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Acid resistant and heat resistant and oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

42.000 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Thread Series Designator:

Nptf 1st end

Specification Data:

Mil-h-3992, type 1, class 1 or 2 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0

Mil-std (military Standard):

Mil-h-3992 spec.