

View Online at <https://aerobasegroup.com/nsn/4720-00-143-9254>

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Temperature Rating:

-40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.000 inches 1st end

Flange Thickness:

0.438 inches 2nd end

Outside Diameter:

1.234 inches

Minimum Inside Bending Radius:

7.380 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

350.0

Bolt Hole Quantity:

2 2nd end

Flange Length:

3.948 inches 1st end

Flange Width:

1.792 inches 2nd end

Connection Style:

Plain 2nd end

Bolt Hole Diameter:

0.438 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Plain face flange 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

2nd layer braided wire and outer layer braided textile yarn and 1st layer braided textile yarn

Maximum Operating Pressure:

800.0 pounds per square inch

Hydrostatic Test Pressure:

1600.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Fuel resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.000 inches working

Flange Style:

Oval 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0