Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-143-9258

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.000 inches 1st end

Flange Thickness:

0.438 inches 1st end

Outside Diameter:

1.234 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

Aligie

0.0

Bolt Hole Quantity:

2 1st end

Flange Length:

3.938 inches 1st end

Flange Width:

1.781 inches 1st end

Connection Style:

Plain swivel 1st end

Bolt Hole Diameter:

0.438 inches 1st end

End Flange Construction:

Split 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Plain face flange 1st end

Burst Test Pressure:

3200.0 pounds per square inch

Layer Composition And Location:

2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord and 1st layer braided cotton cord

Maximum Operating Pressure:

800.0 pounds per square inch

Hydrostatic Test Pressure:

1600.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Nonmetallic Hose Assembly - Page 2 of 2



Outer Covering Environmental Protection:

Oil resistant

Vacuum In Torr:

254.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

10.000 inches working

Flange Style:

Oval 1st end

Media For Which Designed:

Air and fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0