Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-144-4974

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.040 inches
Minimum Inside Bending Radius:
7.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
800.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer braided fiber
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
192.500 inches
Media For Which Designed:
Air and fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0