

View Online at <https://aerobasegroup.com/nsn/4720-00-146-0430>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

3.000 inches

**Tempurature Rating:**

800.0 degrees fahrenheit single response

**Bolt Circle Diameter:**

6.000 inches 2nd end

**Flange Thickness:**

1.000 inches 2nd end

**Outside Diameter:**

3.920 inches

**Minimum Inside Bending Radius:**

23.000 inches

**Inner Conveying Tube Style:**

Annular close-pitch corrugated

**Angle Between Rigid Elbow Fittings In Deg:**

165.0

**Bolt Hole Quantity:**

4 2nd end

**Flange Outside Diameter:**

7.500 inches 2nd end

**Connection Style:**

Raised 2nd end

**Bolt Hole Diameter:**

0.750 inches 2nd end

**Raised Face Height:**

0.500 inches 2nd end

**Raised Face Diameter:**

6.625 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

600.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided nickel copper alloy wire

**Hydrostatic Test Pressure:**

900.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Measuring Method And Length:**

36.900 inches working

**Flange Style:**

Round w/ bolt holes 2nd end

**Special Features:**

Item consists of two identical hoses joined by a 90.0 degrees elbow, one leg having a length of 20.590 in. And the other leg having a length of 15.810 in.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0