Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-147-1694

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.313 inches

#### **Tempurature Rating:**

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.446 inches

Minimum Inside Bending Radius:

4.000 inches

#### **Exterior Color:**

Natural

#### **Connection Style:**

Swivel nut, flareless 1st end

### End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

### **Features Provided:**

Electrostatic discharge capability

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.562 inches 1st end

#### Seat Angle:

12.0 degrees 1st end

## Hydrostatic Test Pressure:

3000.0 pounds per square inch

### **Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant and alcohol resistant and water resistant

### Vacuum In Torr:

50.8

### Inside Surface Condition:

Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length: 16.500 inches working **Thread Series Designator:** Unjf 1st end Specification Data: 96906-ms8006 government standard **Specification Or Standard:** 1 class Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0 Mil-std (military Standard): Mil-h-25579 spec.