Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-147-1700

Round

**Thread Class:** 

3b 1st end

# Thread Direction:

Right-hand 1st end

## Inside Diameter:

0.313 inches

#### **Tempurature Rating:**

-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.446 inches

Minimum Inside Bending Radius:

4.000 inches

#### **Exterior Color:**

Natural

#### **Connection Style:**

Swivel nut, flareless 2nd end

### End Connection Design:

Straight 1st end

## Connection Type:

Threaded internal tube 1st end

## **Features Provided:**

Electrostatic discharge capability

### **Burst Test Pressure:**

9000.0 pounds per square inch

### Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

### Maximum Operating Pressure:

1500.0 pounds per square inch

#### Thread Size:

0.562 inches 2nd end

#### Seat Angle:

12.0 degrees 2nd end

## Hydrostatic Test Pressure:

3000.0 pounds per square inch

### Flow Angle:

90.0 degrees 2nd end

## **Outer Covering Environmental Protection:**

Corrosion resistant and fuel resistant and alcohol resistant and hydraulic solution resistant

### Vacuum In Torr:

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length:

15.000 inches working

Thread Series Designator:

Unjf 1st end

**Specification Data:** 

96906-ms8006 government standard

Specification Or Standard:

1 class

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0