## NSN 4720-00-147-5926

**Cross Sectional Shape:** 

Round

Thread Class: 2b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-147-5926

-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:
1.792 inches
Minimum Inside Bending Radius:
5.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3000.0 pounds per square inch
Maximum Operating Pressure:
750.0 pounds per square inch
Thread Size:
1.000 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1500.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
36.000 inches
Special Features:
Outer layer braided corrosion resistant steel wire; first layer woven glass cloth

## NSN 4720-00-147-5926

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Un 1st end
Specification Data:
30003-2518815-5 manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0